



SyCall Resetable Call Point EN54-11 Approved

The SyCall resettable manual call point is full of innovative features. It has been designed for maximum visibility with high reliability and a pleasant aesthetic appearance and is approved to EN54-11.

There are six modes of operation achievable by simply selecting the appropriate connection terminals at the time of installation. This solution provides flexibility in installation and reduces the number of stocked variants.

The unit has been designed to be highly visible in both the alarm and quiescent state, with a front facing LED, side light tubes and luminescent resettable element, which aid the discovery of an activated call point.

The SyCall call point is also available in a SavWire® and weatherproof version.

Features

- Red surface mount indoor version approved to EN54-11
- High visibility in alarm condition
- Visible in the dark via the luminescent resettable element
- Easy and economical installation
- High impact resistant ABS plastic
- Available in blue, green and yellow
- Six selectable configurations
- Surface and flush mount options
- Easy to reset via the robust twist and set key



Technical

Maximum voltage Vdc	30	
Minimum voltage	4.5V if LED when R1 is chosen	6.0V if LED when R2 is chosen
Current rating		
R1 = 470Ω	18mA @12 Volt - R2	45mA @24 Volt - R1
R2 = 680Ω	13mA @12 Volt - R2	31mA @24 Volt - R2
Weatherproof	3 x 20mm PG glands	
Temperature range °C	-30 to +70	
Protection rating	IP42	
Protection rating (weatherproof)	IP67	
Boxed weight (kg)	0.205	
Boxed weight (kg) weatherproof	0.394	

Part numbers

308-033	Red body, resettable, surface mount(Approved)
308-037	Test keys – pack of 10
308-038	Red body, resettable, weatherproof IP67
308-039	Hinged safety cover
308-040	“NOT IN USE” label (pack of 10)
308-043	Blue body, resettable, surface mount
308-044	Yellow body, resettable surface mount
308-045	Green body, resettable, surface mount
308-078	Flush mount plate
308-079	Red body, resettable flush/surface mount

