



VPR SA4E Spatial Sounder 24Vdc

The SA4E version of the VPR EN54-3 approved sounder has been designed to deliver maximum sound output and achieves a healthy 103dB(A), making it ideal for a wide range of applications such as industrial, security and fire, making the device a truly multi-purpose high output sounder.

Approved to EN54-3 the VPR offers 4 distinctive and selectable tones. Other variants in the range include an approved Dutch sounder and 110/230v AC mains variants. The devices also offer a changeover facility from the Alert to Evacuation tone, when installed using three core cable.

Features

- 4 standard tones and specific Dutch tone
- Synchronised
- Continuously variable volume control
- Designed to work with both conventional and two-wire (SAV-WIRE®) systems
- IP65 specification for all SA4 variants
- Standard base locking system



Technical

Voltage range Vdc	20 - 35
Number of tones	4
Operating frequency - Hz	800 - 1000
Temperature range °C	-20 to +70
Monitoring	Reverse polarity
Protection rating	IP33C
Boxed weight(kg)	0.20

Performance

Version	SA4
Sound output, typical dB(A)	103
Max. current consumption @ 24Vdc mA	32

Part numbers

505-004	EN54-3 Approved Dutch tone, Red body
505-019	110/230Vac 32 tone, Red body
505-020	110/230Vac 32 tone, White body
505-047	EN54-3 Approved Red body, 4 tone,
505-048	EN54-3 Approved White body, 4 tone

