

STI Exit Stopper®

Dimensions and Technical Information

MODELS AVAILABLE

- STI 6400 Exit Stopper - Red
- STI 6402 Exit Stopper - Red, suitable for a double door installation
- Accessories:**
- STI 6400/RK Remote installation kit
(includes 2.4m wire, connecting blocks & fixings)
- STI 6400/RS Remote 95/97 dB sounder
- STI C023/A Spare key
- STI L6400 Alarm warning emergency exit sign
- Options**

| User Programmable Features | JP2 | JP3 | JP4 | JP5 | JP7 |
|----------------------------|-----|-----|-----|-----|-----|
| High Volume* (105 dB) | ON | | | | |
| Low Volume (95 dB) | OFF | | | | |
| Immediate Arming* | | | | | ON |
| 15 Second Arming Delay | | | | | OFF |
| Immediate Activation* | | | | OFF | |
| 15 Second Activation Delay | | | | ON | |
| 30 Second Alarm Duration* | | OFF | OFF | | |
| 180 Second Alarm Duration | | OFF | ON | | |
| Continuous Alarm Duration | | ON | OFF | | |
| Door Prop Mode (5 beeps) | | ON | ON | | |

| | |
|-----------------------------|--|
| Housing | 3mm polycarbonate |
| Power Source | 9 VDC Alkaline |
| Sounder Output (at 1 metre) | 95 dB - low / 105 dB - high |
| Relay Output | 9 VDC, 40mA |
| Dimensions | 136mm/5.35" W X 136mm/5.35" H X 50mm/1.97" D |
| Alarm Current | 200mA |
| Standby Current | 10uA |

* Factory settings

