


Voltage Range
18 - 30VDC



EN54-23



For any technical queries contact
Tel: +44 (0) 1420 592 444
E-mail: technical@cranfordcontrols.com


Doc Ref: 125-119 Issue: 003 Date 09.2020

Made in UK


Full datasheet available - DS139
www.cranfordcontrols.com

VXB-1VAD EN54-23 WALL 2.4-7 BEACON
Approved VXB-1EVAD 24V Beacon
Units are available with Deep or Shallow base,
Lens colour - Red
Flash colour - Red

Voltage Range (VDC): 18 - 30
Temperature Range (°C): -20 to +70
Flash Rate: c.1Hz (Approved)
(Option for 0.5Hz does not comply with EN54-23)
Beacon coverage: W-2.4-7 (Approved)
(Option for W-2.4-4 does not comply with EN54-23)
Coverage volume: 118m³
Max current consumption at 24V: 25mA
Monitoring: Reverse Polarity
Protection Rating: IP33C Deep Base
Protection Rating: IP21C Shallow Base
Boxed Weight (kg): 0.25
Base Diameter (mm): Ø93.0
Material: ABS fire retardant plastic
Maintenance: refer to local test and maintenance guidance



MOUNTING TEMPLATE



1. N/A
2. N/A
3. (-) Neg
4. (-) Neg
5. (+) Positive
6. (+) Positive


DEEP BASE
Part Numbers
126-021 Red, 126-022 White
IP33C / IP65C
0.25kg (boxed)

For locking purposes please
use allen key, not supplied

Voltage Range
18 - 30VDC



EN54-23



For any technical queries contact
Tel: +44 (0) 1420 592 444
E-mail: technical@cranfordcontrols.com


Doc Ref: 125-119 Issue: 003 Date 09.2020

Made in UK


Full datasheet available - DS139
www.cranfordcontrols.com

VXB-1VAD EN54-23 WALL 2.4-7 BEACON
Approved VXB-1EVAD 24V Beacon
Units are available with Deep or Shallow base,
Lens colour - Red
Flash colour - Red

Voltage Range (VDC): 18 - 30
Temperature Range (°C): -20 to +70
Flash Rate: c.1Hz (Approved)
(Option for 0.5Hz does not comply with EN54-23)
Beacon coverage: W-2.4-7 (Approved)
(Option for W-2.4-4 does not comply with EN54-23)
Coverage volume: 118m³
Max current consumption at 24V: 25mA
Monitoring: Reverse Polarity
Protection Rating: IP33C Deep Base
Protection Rating: IP21C Shallow Base
Boxed Weight (kg): 0.25
Base Diameter (mm): Ø93.0
Material: ABS fire retardant plastic
Maintenance: refer to local test and maintenance guidance



MOUNTING TEMPLATE



1. N/A
2. N/A
3. (-) Neg
4. (-) Neg
5. (+) Positive
6. (+) Positive

DEEP BASE
Part Numbers
126-021 Red, 126-022 White
IP33C / IP65C
0.25kg (boxed)

For locking purposes please
use allen key, not supplied